## NSN 4820-00-683-8377

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-683-8377

| Pipe Size Accommodated:                       |
|---|
| 0.750 inches 2nd end                          |
| Thread Direction:                             |
| Right-hand 1st end                            |
| Flow Control Device:                          |
| Disk  |
| Bonnet Type:                                  |
| Inside spring                                 |
| <b>Bonnet Attachment Method:</b>              |
| Threaded                                      |
| Disk Loading Method:                          |
| Spring  |
| Connection Style:                             |
| Plain, optional en (pipe) 2nd end             |
| Valve Operation Method:                       |
| Automatic                                     |
| Connection Type:                              |
| Threaded internal pipe 2nd end                |
| Features Provided:                            |
| Bonnet packing and pressure tight outlet side |
| Thready Qty Per Inch (tpi):                   |
| 14 2nd end                                    |
| Thread Size:                                  |
| 0.750 inches 2nd end                          |
| Opening Pressure Setting:                     |
| 300.0 pounds per square inch                  |
| Special Features:                             |
| Furnished w/ one lift ring                    |
| Material:                                     |
| Stainless steel stem                          |
| Style Designator:                             |
| Angle   |
| Thread Series Designator:                     |
| Npt 1st end                                   |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
|   |
| Demilitarization:                             |
| No  |
| Fiig:   |

A046b0