## NSN 4820-00-683-9348

Pressure And Temperature Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-683-9348

**Body Material:** 

Bronze, astm b61 and bronze, astm b62

**Body Style:** 

Tee w/ offset give "adqm" "adqn" and "adqp" only if flanged all ends

Stem Material:

Bronze, astm b61 and bronze, astm b62

**Furnished Items:** 

Emergency opening device

**Tempurature Rating:** 

210.0 degrees fahrenheit

Media For Which Designed:

Water, fresh

**First End Connection Type:** 

Threaded internal pipe

First End Style Designator:

Plain

First End Pipe Size Accommodated:

0.750 inches

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Identical

Third End Relationship With Preceding Ends:

Identical with first end

**Seat Material:** 

Bronze, astm b61 and bronze, astm b62

Offset Distance:

0.625 inches

Flow Control Device:

Poppet

Flow Control Device Material:

Nickel copper alloy

**End Connection Quantity:** 

3

**Opening Pressure Setting:** 

125.0 pounds per square inch

**Bulb Length:** 

5.625 inches

**Tempurature Adjustability:** 

Not adjustable

**Tempurature Control Device Type:** 

Thermostatic

## NSN 4820-00-683-9348

Pressure And Temperature Relief Valve - Page 2 of 2



<b>Special</b>	Features:
----------------	-----------

75.000 btu per hr mindischarge

**Specification Or Standard:** 

1 type and b style and 2 class and x size

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A07100