# NSN 4820-00-684-0122

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-684-0122

# Thread Direction:

Right-hand all ends

## **Flow Control Device:**

Disk

## Bonnet Type:

Inside spring

## **Bonnet Attachment Method:**

Threaded

## **Disk Loading Method:**

Spring

### Valve Discharge Flow Rate:

3.0 gallons per minute

### **Connection Style:**

Plain, optional en (pipe) all ends

### Valve Operation Method:

Manual or automatic

## **Connection Type:**

Threaded internal pipe all ends

### Features Provided:

Valve stem lock shield and bonnet packing and pressure tight outlet side

### Thready Qty Per Inch (tpi):

18 all ends

### Maximum Operating Pressure:

1000.0 pounds per square inch single response

#### Thread Size:

0.250 inches all ends

### **Opening Pressure Setting:**

350.0 pounds per square inch

#### Material:

Steel seat

### Media For Which Designed:

Water-oil-gas single response

#### Style Designator:

Angle

## **Thread Series Designator:**

Npt all ends

# Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

# NSN 4820-00-684-0122

Safety Relief Valve - Page 2 of 2

**Fiig:** A046b0

