NSN 4820-00-684-4271

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-684-4271

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Disk Loading Method:

Spring

Maximum Operating Temp:

160.0 degrees fahrenheit 2nd response

Connection Style:

Flared (tube) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

12 all ends

Maximum Operating Pressure:

300.0 pounds per square inch single response

Thread Size:

1.312 inches all ends

Seat Angle:

37.0 degrees all ends

Material:

Aluminum flow control device

Material Specification:

Qq-a-225/5, alloy 2017, t4 federal specification single material response seat

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Un all ends

Specification Data:

96906-ms28884b-16 manufacturers standard

NSN 4820-00-684-4271

Check Valve - Page 2 of 2

Specification Or Standard:

B class and 1.000 size

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-s-5059 spec.

