NSN 4820-00-684-4782

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-684-4782 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.028 inches Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Flareless all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.438 inches all ends Seat Angle: 12.0 degrees all ends Material: Steel comp 303 flow control device **Material Specification:** Qq-a-225/6, alloy 2024, t351 federal specification single material response body Media For Which Designed: Hydraulic fluid, petroleum base single response **Style Designator:** Straight thru **Thread Series Designator:** Unjf all ends Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 4820-00-684-4782

Restrictor Check Valve - Page 2 of 2



Fiig:

A530b0

Mil-std (military Standard):

Mil-s-7720 spec.