NSN 4820-00-684-4782

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-684-4782

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Aperture Diameter:

0.028 inches

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

Flareless all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.438 inches all ends

Seat Angle:

12.0 degrees all ends

Material:

Steel comp 303 flow control device

Material Specification:

Qq-a-225/6, alloy 2024, t351 federal specification single material response body

Media For Which Designed:

Hydraulic fluid, petroleum base single response

Style Designator:

Straight thru

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4820-00-684-4782

Restrictor Check Valve - Page 2 of 2

Fiig: A530b0

Mil-std (military Standard):

Mil-s-7720 spec.

