NSN 4820-00-689-1345

Safety Relief Valve - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/4820-00-689-1345

Pipe Size Accommodated:
0.375 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st endplain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st endthreaded internal pipe 2nd end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 2nd end
Maximum Operating Pressure:
2500.0 pounds per square inch single response
Thread Size:
0.375 inches 1st end
Opening Pressure Setting:
200.0 pounds per square inch
Material:
Steel comp 316
Material Specification:
Fed standard 66, aisi 316/sae 30316 federal standard single material response
Media For Which Designed:
Air 1st responseacetylene 2nd responseammonia, gaseous 3rd responserefrigerant 12 4th responsehydrogen 5th response
Style Designator:
Straight through note: to be used for valve bodies of separable sections.
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:

NSN 4820-00-689-1345

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0