

View Online at <https://aerobasegroup.com/nsn/4820-00-689-3207>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

14 1st end

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Special Features:

Valve size 0.750 in.

Material:

Copper alloy body

Material Specification:

Qq-c-390, alloy d4 federal specification all material responses

Media For Which Designed:

Steam single response

Style Designator:

Straight thru

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources 79911 have indicated thier part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Npt all ends

Specification Data:

59646-mss sp-80 professional/industrial association standard

Specification Or Standard:

1 type and 200psi class and b end and 0.750 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0