## NSN 4820-00-691-6362

Check Valve - Page 1 of 2

Thread Class: 3b 1st end

Poppet

Thread Direction:
Right-hand 1st end
Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-00-691-6362

Disk Loading Method:					
Spring					
Maximum Operating Temp:					
325.0 degrees fahrenheit 2nd response					
Connection Style:					
Flareless 2nd end					
Valve Operation Method:					
Automatic					
Connection Type:					
Threaded internal tube 1st end					
Mounting Position:					
Horizontal					
Valve Size:					
0.875 inches					
Thready Qty Per Inch (tpi):					
12 2nd end					
Maximum Operating Pressure:					
60.0 pounds per square inch single response					
Thread Size:					
1.312 inches 2nd end					
Seat Angle:					
12.0 degrees 2nd end					
Face To Face Distance:					
4.000 inches					
Outside Diameter Tube Accommodated:					
1.000 inches 1st end					
Material:					
Aluminum alloy					
Media For Which Designed:					
Fuel/oil, hydrocarbon single response					
Surface Treatment:					
Anodize					
Style Designator:					
Straight through flanged ends					
Thread Series Designator:					
Unj 2nd end					

## NSN 4820-00-691-6362

Check Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A530b0