## NSN 4820-00-703-8936

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-703-8936 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 16 all ends **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.500 inches all ends **Special Features:** Second end rulkhead type per ms33657 Material: Aluminum alloy seat Media For Which Designed: Oil, hydraulic single response **Surface Treatment: Thread Series Designator:** 

Anodize **Style Designator:** Straight thru Unf all ends Shelf Life: N/a

## NSN 4820-00-703-8936

Check Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A530b0