

View Online at <https://aerobasegroup.com/nsn/4820-00-705-1645>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

0.375 inches

Maximum Operating Pressure:

700.0 pounds per square inch single response

Outside Diameter:

3.750 inches all ends

Face To Face Distance:

6.000 inches

Thickness:

0.562 inches all ends

Bolt Hole Diameter:

0.635 inches all ends

Bolt Circle Diameter:

2.625 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches all ends

Raised Face Diameter:

1.375 inches all ends

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Straight through flanged ends

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 74965, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0