NSN 4820-00-715-4576

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-715-4576

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Unable To Decode:
Unable to decode and unable to decode
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Connection Style:
Flared (tube) 2nd end
Connection Type:
Threaded external tube 2nd end
Mounting Facility:
Bracket
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
18 2nd end
Maximum Operating Pressure:
35.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Face To Face Distance:
1.960 inches
Outside Diameter Tube Accommodated:
0.500 inches 1st end
Special Features:
Valve operation method: hydraulic
Material:
Steel comp 303 flow control device
Material Specification:
Qq-a-225/6 federal specification single material response body
Media For Which Designed:
Oil, hydraulic single response
Style Designator:
Straight thru
-

NSN 4820-00-715-4576

Restrictor Check Valve - Page 2 of 2



Thread Series Designa	tor:
-----------------------	------

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0