NSN 4820-00-719-5573

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-719-5573 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 2.5 gallons per minute **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 20 all ends **Adjustable Pressure Range:** +1400.0/+2300.0 pounds per square inch **Thread Size:** 0.437 inches all ends **Opening Pressure Setting:** 1550.0 pounds per square inch Material: Stainless steel flow control device **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Unjf all ends Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 4820-00-719-5573

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.