

View Online at <https://aerobasegroup.com/nsn/4820-00-720-3991>

**Thread Class:**

3a all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

160.0 degrees fahrenheit 2nd response

**Connection Style:**

Flareless all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube all ends

**Mounting Position:**

Horizontal or vertical

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.562 inches all ends

**Seat Angle:**

12.0 degrees all ends

**Special Features:**

3.5 gpm rated flow capacity

**Material:**

Aluminum alloy

**Media For Which Designed:**

Hydraulic fluid, petroleum base single response

**Surface Treatment:**

Anodize

**Style Designator:**

Straight thru

**Test Data Document:**

81349-mil-v-5524 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unjf all ends

**Specification Or Standard:**

B style and 3000 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530b0