## NSN 4820-00-720-4264

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-720-4264 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** Flareless all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends Seat Angle: 37.0 degrees all ends **Outside Diameter Tube Accommodated:** 0.250 inches all ends Material: Stainless steel flow control device **Material Specification:** Qq-a-22516, alloy 2024, t4 federal specification single material response body Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Style Designator:** Straight thru **Thread Series Designator:** Unf all ends Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 4820-00-720-4264

Restrictor Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0