NSN 4820-00-720-4978

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-720-4978

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

200.0 degrees fahrenheit single response

Connection Style:

Flared (tube) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

600.0 pounds per square inch single response

Thread Size:

0.562 inches all ends

Seat Angle:

37.0 degrees all ends

Opening Pressure Setting:

8.0 pounds per square inch

Material:

Rubber butadiene-acrylonitrile class nbr seat

Material Specification:

Qq-a-225/6 federal specification single material response body

Media For Which Designed:

Hydrogen 5th response

Style Designator:

Straight thru

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4820-00-720-4978

Check Valve - Page 2 of 2

Fiig: A530b0

Mil-std (military Standard):

Mil-p-5516 spec.

