NSN 4820-00-724-7632

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-724-7632

Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
12.0 gallons per minute
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
16 all ends
Maximum Operating Pressure:
4000.0 pounds per square inch single response
Thread Size:
0.750 inches all ends
Opening Pressure Setting:
4800.0 pounds per square inch
Material:
Stainless steel flow control device
Media For Which Designed:
Air single response
Style Designator:
Straight through note: to be used for valve bodies of separable sections.
Thread Series Designator:
Unjf all ends
Shelf Life:
N/a

NSN 4820-00-724-7632

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0