NSN 4820-00-724-7632

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-724-7632

Thread Class: 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Poppet **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring Valve Discharge Flow Rate: 12.0 gallons per minute Maximum Operating Temp: 275.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends Valve Operation Method: Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 4000.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Opening Pressure Setting:** 4800.0 pounds per square inch Material: Stainless steel flow control device Media For Which Designed: Air single response **Style Designator:** Straight through note: to be used for valve bodies of separable sections. **Thread Series Designator:** Unjf all ends Shelf Life:

N/a

NSN 4820-00-724-7632

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

