NSN 4820-00-727-8028

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-727-8028

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 2nd end
Maximum Operating Pressure:
50.0 pounds per square inch single response
Thread Size:
0.250 inches 2nd end
Opening Pressure Setting:
25.0 pounds per square inch
Material:
Steel comp 303 and rubber butadiene-acrylonitrile class nbr flow control device
Material Specification:
Fed standard 66 federal standard 1st material response flow control device
Media For Which Designed:
Gas, natural 2nd response
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

NSN 4820-00-727-8028

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0