## NSN 4820-00-728-1025



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-728-1025 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 20 all ends **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends **Opening Pressure Setting:** 3330.0 pounds per square inch Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Style Designator:** Angle **Thread Series Designator:** Unf all ends Shelf Life:

N/a **Unit Of Measure:** 

## NSN 4820-00-728-1025

Safety Relief Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A046b0