NSN 4820-00-729-5452



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-729-5452 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 7.0 gallons per minute **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 1st end Thready Qty Per Inch (tpi): 18 1st end Adjustable Pressure Range: +1400.0/+2300.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Opening Pressure Setting:** 1550.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.375 inches 1st end Material: Stainless steel flow control device **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Unjf 1st end Shelf Life:

Unit Of Measure:

N/a

NSN 4820-00-729-5452

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.