NSN 4820-00-730-8966

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-730-8966

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
60.0 cubic feet per minute
Maximum Operating Temp:
185.0 degrees fahrenheit single response
End Application:
Missile, aim-9 system (sidewinder)
Connection Style:
Plain (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe all ends
Features Provided:
Valve stem lock shield and bonnet packing
Adjustable Pressure Range:
+2000.0/+6500.0 pounds per square inch
Maximum Operating Pressure:
6500.0 pounds per square inch single response
Thread Size:
0.250 inches all ends
Material:
Stainless steel body
Media For Which Designed:
Air single response
Surface Treatment:
Surface Treatment: Passivate
Passivate
Passivate Style Designator:

NSN 4820-00-730-8966

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0