NSN 4820-00-740-6565



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-740-6565 **Thread Direction:** Right-hand all ends **Flow Control Device: Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 225.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe all ends **Features Provided:** Valve stem lock shield and bonnet packing and pressure tight outlet side **Adjustable Pressure Range:** +4.0/+15.0 pounds per square inch **Maximum Operating Pressure:** 3100.0 pounds per square inch single response **Thread Size:** 0.125 inches all ends **Opening Pressure Setting:** 10.0 pounds per square inch Material: Stainless steel stem Media For Which Designed: Water-oil-gas single response **Surface Treatment:** Anodize **Style Designator:** Angle **Thread Series Designator:** Npt all ends Shelf Life:

Unit Of Measure:

N/a

NSN 4820-00-740-6565

Safety Relief Valve - Page 2 of 2



Demi			

No

Fiig:

A046b0