## NSN 4820-00-740-6565

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-740-6565

Thread Direction	on:
Right-hand all e	inds
Flow Control D	Device:
Poppet	
Bonnet Type:	
Inside spring	
Bonnet Attach	ment Method:
Integral	
Disk Loading N	Method:
Spring	
Maximum Ope	rating Temp:
225.0 degrees f	ahrenheit single response
Connection Sty	yle:
Plain, optional e	en (pipe) all ends
Valve Operatio	n Method:
Automatic	
Connection Ty	pe:
Threaded intern	al pipe all ends
Features Provi	ded:
Valve stem lock	shield and bonnet packing and pressure tight outlet side
Adjustable Pre	essure Range:
+4.0/+15.0 pour	nds per square inch
Maximum Ope	rating Pressure:
3100.0 pounds	per square inch single response
Thread Size:	
0.125 inches all	ends
Opening Press	sure Setting:
10.0 pounds pe	r square inch
Material:	
Stainless steel s	stem
Media For Whie	ch Designed:
Water-oil-gas si	ngle response
Surface Treatm	nent:
Anodize	
Style Designat	or:
Angle	
Thread Series	Designator:
Npt all ends	
Shelf Life:	

---

## NSN 4820-00-740-6565

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

