NSN 4820-00-752-8967

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-752-8967

Pipe Size Accommodated:

0.500 inches 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Maximum Operating Temp:

3400.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe 2nd end

Features Provided:

Bonnet packing and pressure tight outlet side

Adjustable Pressure Range:

+60.0/+175.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Material:

Copper alloy body

Media For Which Designed:

Fuel/oil, hydrocarbon 1st response

Style Designator:

Angle

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4820-00-752-8967

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

