NSN 4820-00-752-9338

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-752-9338

View Online at https://aerobasegroup.com/nsn/4820-00-752-9338
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.500 inches all ends
Seat Angle:
12.0 degrees all ends
Special Features:
2.3 gpm rated flow capacity
Media For Which Designed:
Hydraulic fluid, petroleum base single response
Style Designator:
Straight thru
Test Data Document:
81349-mil-v-5524 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unjf all ends
Specification Or Standard:
B style and 3000 class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-00-752-9338

Check Valve - Page 2 of 2



Fiig:

A530b0