

View Online at <https://aerobasegroup.com/nsn/4820-00-752-9438>

Body Material:

Bronze, mil-b-16541, grade a

First End Flange Outside Diameter:

9.062 inches

Second End Flange Outside Diameter:

9.062 inches

Body Style:

Straight thru

Stem Material:

Nickel copper alloy, mil-n-894

Media For Which Designed:

Water, salt

First End Connection Type:

Plain face flange

First End Style Designator:

Plain

First End Flange Shape Style:

Round w/ bolt holes

First End Flange Thickness:

1.062 inches

First End Bolt Hole Quantity:

10

First End Bolt Hole Diameter:

0.688 inches

First End Bolt Circle Diameter:

7.812 inches

Second End Relationship With First End:

Not identical

Second End Connection Type:

Plain face flange

Second End Style Designator:

Plain

Second End Flange Shape Style:

Round w/ bolt holes

Second End Flange Thickness:

0.562 inches

Second End Bolt Hole Quantity:

10

Second End Bolt Hole Diameter:

0.688 inches

Second End Bolt Circle Diameter:

7.812 inches

Seat Material:

Nickel copper alloy, mil-n-894

Face To Face Distance:

15.000 inches

Flow Control Device:

Disk, bottom guided

Flow Control Device Material:

Rubber, mil-r-2765

End Connection Quantity:

2

Renewable Seat Ring Type:

Pressed-in

Outlet Pressure Range:

+25.0 to 60.0 pounds per square inch

Regulation Type:

Automatic single stage

Valve Stem Design:

Single seat

Valve Loading Method:

Spring

Maximum Inlet Pressure Rating:

250.0 pounds per square inch

Outlet Pressure Accuracy Rating:

Not rated

Filter:

Not included

Reference Number Differentiating Characteristics:

As differentiated by outlet pressure range

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100