NSN 4820-00-752-9526

Stop-check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-752-9526

| Pipe Size Accommodated: |
|---|
| 1.000 inches all ends |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Maximum Operating Temp: |
| 775.0 degrees fahrenheit single response |
| Connection Style: |
| Socket (pipe) all ends |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Unthreaded internal pipe all ends |
| Mounting Position: |
| Horizontal or vertical |
| Features Provided: |
| Bonnet packing |
| Maximum Operating Pressure: |
| 600.0 pounds per square inch single response |
| Material: |
| Steel seat |
| Material Specification: |
| Mil-r-17131, mil-rcocr-a military specification single material response seat |
| Media For Which Designed: |
| Steam single response |
| Style Designator: |
| Straight thru |
| Specification Or Standard: |
| D composition |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A530b0 |
| Mil-std (military Standard): |

Mil-r-17131 spec.