## NSN 4820-00-755-7085



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-755-7085 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring Valve Discharge Flow Rate: 5.0 cubic feet per minute **Connection Style:** External seat for gasket seal (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external boss 1st end **Thread Size:** 0.562 inches 1st end **Opening Pressure Setting:** 35.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.375 inches 1st end Material: Aluminum alloy 2024 body **Material Specification:** Qq-a-250/4, alloy2024 federal specification single material response seat **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Angle **Thread Series Designator:** Unjf 1st end Shelf Life:

**Unit Of Measure:** 

N/a

## NSN 4820-00-755-7085

Safety Relief Valve - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.