NSN 4820-00-755-7085

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-755-7085

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

5.0 cubic feet per minute

Connection Style:

External seat for gasket seal (boss) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external boss 1st end

Thread Size:

0.562 inches 1st end

Opening Pressure Setting:

35.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Material:

Aluminum alloy 2024 body

Material Specification:

Qq-a-250/4, alloy2024 federal specification single material response seat

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Angle

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4820-00-755-7085

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.

