## NSN 4820-00-756-0769

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-756-0769

Pipe	Size	Accommodated:

0.250 inches 1st end

**Thread Direction:** 

Right-hand 1st end

## Flow Control Device:

Poppet

## **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

250.0 degrees fahrenheit 2nd response

#### **Connection Style:**

Plain (pipe) 1st end

#### Valve Operation Method:

Automatic

#### **Connection Type:**

Threaded external pipe 1st end

## Adjustable Pressure Range:

+2.0/+6.0 pounds per square inch

## Maximum Operating Pressure:

200.0 pounds per square inch single response

## Thread Size:

0.250 inches 1st end

## **Opening Pressure Setting:**

4.0 pounds per square inch

### **Special Features:**

Pop-off type

Material:

Steel comp 303 seat

### **Material Specification:**

Fed standard 66 federal standard single material response body

### Media For Which Designed:

Hydrogen 5th response

#### Surface Treatment:

Passivate

### Style Designator:

Straight through note: to be used for valve bodies of one section only.

## **Thread Series Designator:**

Npt 1st end

Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 4820-00-756-0769

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

