## NSN 4820-00-756-1843

Check Valve - Page 1 of 2



5
View Online at https://aerobasegroup.com/nsn/4820-00-756-1843
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit 2nd response
Connection Style:
Flareless 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
16 2nd end
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Thread Size:
0.875 inches 1st end
Seat Angle:
12.0 degrees 2nd end
Outside Diameter Tube Accommodated:
0.625 inches 1st end
Special Features:
Bulkhead fitting on first end
Material:
Steel comp 440a flow control device
Material Specification:
Qq-a-225/6, alloy 2024, t4 federal specification single material response seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Style Designator:
Angle
Thread Series Designator:
Unf 2nd end

## NSN 4820-00-756-1843

Check Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A530b0

