

View Online at <https://aerobasegroup.com/nsn/4820-00-756-1843>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

275.0 degrees fahrenheit 2nd response

**Connection Style:**

Flareless 2nd end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 2nd end

**Mounting Position:**

Horizontal or vertical

**Thready Qty Per Inch (tpi):**

16 2nd end

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Thread Size:**

0.875 inches 1st end

**Seat Angle:**

12.0 degrees 2nd end

**Outside Diameter Tube Accommodated:**

0.625 inches 1st end

**Special Features:**

Bulkhead fitting on first end

**Material:**

Steel comp 440a flow control device

**Material Specification:**

Qq-a-225/6, alloy 2024, t4 federal specification single material response seat

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Surface Treatment:**

Anodize

**Style Designator:**

Angle

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530b0