

View Online at <https://aerobasegroup.com/nsn/4820-00-757-4329>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Maximum Operating Temp:

225.0 degrees fahrenheit single response

Connection Style:

Flared (tube) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Features Provided:

Bonnet packing and pressure tight outlet side

Adjustable Pressure Range:

+4.0/+15.0 pounds per square inch

Maximum Operating Pressure:

3100.0 pounds per square inch single response

Thread Size:

0.437 inches all ends

Seat Angle:

37.0 degrees all ends

Opening Pressure Setting:

10.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.250 inches all ends

Material:

Rubber butadiene-acrylonitrile class nbr flow control device

Media For Which Designed:

Water-oil-gas single response

Surface Treatment:

Anodize

Style Designator:

Angle

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0