

View Online at <https://aerobasegroup.com/nsn/4820-00-758-9285>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Pressed-in

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Manual

Connection Type:

Threaded external tube 2nd end

Mounting Position:

Horizontal

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

16 1st end

Maximum Operating Pressure:

60.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Special Features:

Bulkhead thd located on first end, 3/4-16 unf3a, 0.358 in. Min, 0.425 in. Maximum lg

Material:

Stainless steel flow control device

Material Specification:

Mil-p-5315 military specification single material response

Media For Which Designed:

Oil, lubricating, diester base single response

Surface Treatment:

Anodize

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-p-5315 spec.