NSN 4820-00-760-7677



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-760-7677 **Thread Direction:** Right-hand all ends **Flow Control Device: Poppet Bonnet Type:** Inside screw **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 225.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe all ends **Features Provided:** Pressure tight outlet side **Adjustable Pressure Range:** +800.0/+1500.0 pounds per square inch **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.125 inches all ends **Opening Pressure Setting:** 1000.0 pounds per square inch Material: Steel comp 303 **Material Specification:** 66 federal standard single material response Media For Which Designed: Fuel/oil, hydrocarbon 1st response **Surface Treatment: Passivate Style Designator:** Angle **Thread Series Designator:** Anpt all ends

Shelf Life:

N/a

NSN 4820-00-760-7677

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0