NSN 4820-00-762-1203

Globe Valve - Page 1 of 2

A046b0



View Online at https://aerobasegroup.com/nsn/4820-00-762-1203

view Offilite at https://defobasegroup.com/hish/4020-00-702-1200
Pipe Size Accommodated:
2.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Pressure seal, ring type
Maximum Operating Temp:
775.0 degrees fahrenheit single response
Connection Style:
Beveled (pipe) all ends
Valve Operation Method:
Manual
Connection Type:
Butt weld pipe all ends
Features Provided:
Bonnet packing
Maximum Operating Pressure:
600.0 pounds per square inch single response
Special Features:
Valve size 2.500 in.; non-revolving stem
Material:
Steel seat
Material Specification:
Mil-r-17131 military specification single material response seat
Media For Which Designed:
Steam single response
Style Designator:
Straight thru
Test Data Document:
81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Furnished Items And Quantity:
1 handwheel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

NSN 4820-00-762-1203

Globe Valve - Page 2 of 2



Mil-std (military Standard):

Mil-r-17131 spec.