

View Online at <https://aerobasegroup.com/nsn/4820-00-762-1204>

Pipe Size Accommodated:

3.000 inches all ends

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Pressure seal, ring type

Maximum Operating Temp:

775.0 degrees fahrenheit single response

Connection Style:

Beveled (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Butt weld pipe all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Special Features:

Valve size 3.000 in.; stem is non-revolving, resulting in lower friction of all rotating parts; top and bottom guided disc assures stem operation without side thrust

Material:

Steel uns j03002 body

Material Specification:

Mil-r-17131 military specification single material response flow control device

Media For Which Designed:

Steam single response

Special Test Features:

Radiography inspection per mil-std-271

Style Designator:

Straight thru

Test Data Document:

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-4-17131 spec.