

View Online at <https://aerobasegroup.com/nsn/4820-00-762-1213>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

6 all ends

Maximum Operating Temp:

425.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Features Provided:

Bonnet packing

Valve Size:

2.000 inches

Maximum Operating Pressure:

200.0 pounds per square inch single response

Outside Diameter:

5.938 inches all ends

Face To Face Distance:

10.250 inches

Thickness:

0.812 inches all ends

Bolt Hole Diameter:

0.688 inches all ends

Bolt Circle Diameter:

4.625 inches all ends

Flange Face Design:

Plain all ends

Special Features:

Valve size 1-1/2 in.

Material:

Nickel alloy flow control device

Material Specification:

Qq-c-390c, alloy d4 federal specification single material response body

Media For Which Designed:

Steam single response

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0