

View Online at <https://aerobasegroup.com/nsn/4820-00-762-1356>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

160.0 degrees fahrenheit single response

Connection Style:

Flared (tube) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Seat Angle:

37.0 degrees all ends

Material:

Steel comp 303 flow control device and steel comp 304 flow control device and rubber butadiene-acrylonitrile class nbr flow control device

Material Specification:

Qq-s-764, type 303-canceled federal specification 1st material response flow control device and qq-s-763, class 304 federal specification 2nd material response flow control device

Media For Which Designed:

Oil, lubricating, diester base 2nd response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.