## NSN 4820-00-762-9701

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-762-9701

Pipe Size Accommodated:
1.250 inches 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
165.0 degrees fahrenheit single response
End Application:
Fleet modernization program-cruisers/destroyers
Connection Style:
Streamlined with two brazing rings err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+501.0/+800.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Special Features:
Hand lifting devise is required
Material:
Plastic polytetrafluoroethylene flow control device
Material Specification:
Qq-c-390, alloy d4/d federal specification single material response seat
Media For Which Designed:
Alcohol, ethyl single response
Style Designator:
Angle
Test Data Document:
81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-762-9701

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0