NSN 4820-00-763-5064



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-763-5064 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Poppet **Disk Loading Method:** Spring **Maximum Operating Temp:** 350.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends **Maximum Operating Pressure:** 100.0 pounds per square inch single response **Thread Size:** 1.062 inches all ends Seat Angle: 37.0 degrees all ends **Special Features:** Hot air media; critical application, mcdonnel aircraft models f4, rf4, and yf4 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, alloy 2024 federal specification single material response Media For Which Designed: Air single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Un all ends

NSN 4820-00-763-5064

Check Valve - Page 2 of 2



Shelf	Life:
•	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.