NSN 4820-00-764-3294

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-764-3294

| Pipe Size Accommodated: |
|--|
| 0.125 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Disk Loading Method: |
| Spring |
| Connection Style: |
| Plain (pipe) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external pipe 1st end |
| Mounting Position: |
| Horizontal or vertical |
| Thready Qty Per Inch (tpi): |
| 27 1st end |
| Maximum Operating Pressure: |
| 2100.0 pounds per square inch single response |
| Thread Size: |
| 0.125 inches 1st end |
| Material: |
| Stainless steel |
| Material Specification: |
| Mil-s-7720, comp 302 military specification single material response |
| Media For Which Designed: |
| Oxygen, gaseous single response |
| Surface Treatment: |
| Passivate |
| Style Designator: |
| Straight thru |
| Supplementary Features: |
| Flow control device: plug |
| Thread Series Designator: |
| Anpt 1st end |
| Furnished Items And Quantity: |
| 1 cap and 1 chain |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Yes - demil/mli

NSN 4820-00-764-3294

Check Valve - Page 2 of 2



Fiig:

A530b0

Mil-std (military Standard):

Mil-s-7720 spec.