NSN 4820-00-768-3649

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-768-3649

Pipe Size Accommodated:
0.750 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
293.0 pounds per hour
Maximum Operating Temp:
406.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Thready Qty Per Inch (tpi):
14 2nd end
Adjustable Pressure Range:
+1.0/+300.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
0.750 inches 2nd end
Opening Pressure Setting:
50.0 pounds per square inch
Special Features:
Lifting lever
Material:
Copper alloy
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-00-768-3649

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0