

m/nsn/4820-00-770-3711

| NSN 4820-00-770-3711 Check Valve - Page 1 of 2 |
|--|
| View Online at https://aerobasegroup.com/nsn/4 |
| Thread Class: |
| 3a all ends |
| Thread Direction: |
| Right-hand all ends |
| Flow Control Device: |
| Cone |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 65.0 degrees fahrenheit 1st response |
| Connection Style: |
| Flared (tube) all ends |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external tube all ends |
| Mounting Facility: |
| Threaded fastener |
| Mounting Position: |
| Horizontal or vertical |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 0.562 inches all ends |
| Seat Angle: |
| 37.0 degrees all ends |
| Special Features: |
| 4 ports in accordance with ms33656e4 |
| Material: |
| Stainless steel |
| Media For Which Designed: |
| Air single response |
| |

Style Designator:

Cross

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4820-00-770-3711

Check Valve - Page 2 of 2

Fiig: A530b0

