NSN 4820-00-772-0623

Globe Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-00-772-0623

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 2nd end

Width:

3.580 inches 2nd end

Length:

5.750 inches 2nd end

Valve Operation Method:

Manual

Flange Shape:

Rectangular with holes 2nd end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Maximum Operating Pressure:

700.0 pounds per square inch single response

Outside Diameter:

4.625 inches 1st end

Thickness:

0.750 inches 2nd end

Bolt Hole Diameter:

0.750 inches 1st end

Bolt Circle Diameter:

3.250 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

0.625 inches 2nd end

Center To Center Distance Between Bolt Holes Along Width:

2.406 inches 2nd end

Flange Face Design:

Raised straight 2nd end

Raised Face Height:

0.275 inches 1st end

Raised Face Diameter:

0.750 inches 2nd end

Special Features:

Outlet has 2 holes



NSN 4820-00-772-0623

Globe Valve - Page 2 of 2

Material:

Steel stem

Media For Which Designed:

Steam single response

Style Designator:

Cross

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

