NSN 4820-00-774-9538

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-774-9538

Pipe Size Accommodated:
1.125 inches 2nd end
Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+1501.0/+2000.0 pounds per square inch
Maximum Operating Pressure:
4000.0 pounds per square inch single response
Special Features:
As modified by pac aajj
Material:
Steel uns j92650 flow control device
Material Specification:
Qq-c-390, alloy d4/d federal specification single material response body
Media For Which Designed:
Air single response
Style Designator:
Angle
Furnished Items And Quantity:
2 nut and 1 wrench
Specification Or Standard:
A1 type and c class
Shelf Life:
N/a

NSN 4820-00-774-9538

Safety Relief Valve - Page 2 of 2



Unit	Of N	leası	ıre:
------	------	-------	------

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-867 spec.