

View Online at <https://aerobasegroup.com/nsn/4820-00-775-9001>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

0.1 cubic meters per minute

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

165.0 degrees fahrenheit single response

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Features Provided:

Valve stem lock shield and pressure tight outlet side

Thready Qty Per Inch (tpi):

24 2nd end

Adjustable Pressure Range:

+170.0 to 180.0 pounds per square inch

Maximum Operating Pressure:

175.0 pounds per square inch single response

Thread Size:

0.625 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Opening Pressure Setting:

170.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.375 inches 2nd end

Material:

Rubber synthetic seat

Material Specification:

Qq-a-225/6, t4 federal specification single material response body

Media For Which Designed:

Oil, hydraulic single response

Surface Treatment:

Anodize

Style Designator:

Err-090

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0