

View Online at <https://aerobasegroup.com/nsn/4820-00-775-9001>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

0.1 cubic meters per minute

**Renewable Seat Ring Type:**

Pressed-in

**Maximum Operating Temp:**

165.0 degrees fahrenheit single response

**Connection Style:**

Flared (tube) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 1st end

**Features Provided:**

Valve stem lock shield and pressure tight outlet side

**Thready Qty Per Inch (tpi):**

24 2nd end

**Adjustable Pressure Range:**

+170.0 to 180.0 pounds per square inch

**Maximum Operating Pressure:**

175.0 pounds per square inch single response

**Thread Size:**

0.625 inches 2nd end

**Seat Angle:**

37.0 degrees 1st end

**Opening Pressure Setting:**

170.0 pounds per square inch

**Outside Diameter Tube Accommodated:**

0.375 inches 2nd end

**Material:**

Rubber synthetic seat

**Material Specification:**

Qq-a-225/6, t4 federal specification single material response body

**Media For Which Designed:**

Oil, hydraulic single response

**Surface Treatment:**

Anodize

**Style Designator:**

Err-090

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0