NSN 4820-00-776-6886

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-776-6886 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 300.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Features Provided:** Pressure tight outlet side Adjustable Pressure Range: +265.0/+380.0 pounds per square inch **Maximum Operating Pressure:** 2500.0 pounds per square inch single response **Thread Size:** 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end **Opening Pressure Setting:** 350.0 pounds per square inch Material: Aluminum alloy Media For Which Designed: Hydraulic fluid, silicate-ester base single response **Surface Treatment:** Anodize **Style Designator:** Straight through note: to be used for valve bodies of one section only. **Thread Series Designator:** Unjf 1st end

Shelf Life: N/a **Unit Of Measure:**

NSN 4820-00-776-6886

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0